

## Belt grinder

# 00103067

### TAS Belt grinders - TAS 75X

HM TAS 75X is an efficient quality belt sander with built-in double extraction for optimal grinding in all metals.

HM TAS 75X is designed according to the strictest environmental and safety regulations.

HM TAS 75X is equipped as standard with extraction, motor brake, tiltable sanding plane, eye protection, angle stop and motor protection with zero voltage release.

The machine is also CE-approved and has a low level of noise in the operator's place.

#### Standard features :

- Danish design and top quality.
- Dust extraction
- Powerful motors
- Thermal Overload No Volt Release starter
- Separate emergency stop
- Electronic Motor-brake
- Adjustable top work support
- Eye protection
- Working height can be set to the most optimum position
- Unique design for clean, quick and safe grinding
- Self-adjusting belt tensioner

#### Optional accessories :

- Centerless grinding attachments (dry or wet)
- Pipe notching attachment

#### Product Link:

<https://dev.hmmachinery.dk/en/product/belt-grinder-673>

## Product Specification

Motor (HP)	4,1
Voltage	3x400V-50 Hz
Wheel size, Drive wheel (ø mm)	200x75x24
Wheel size, Contact wheel (ø mm)	200x75x20
Grinder Belt (mm)	75x2000
Grinding table (mm)	75x605
Exhaust (m <sup>3</sup> /h)	630
With exhaust	1
Length (mm)	1025
Width (mm)	500
Height (mm)	1000
Net weight (kg)	90

### Product Link:

<https://dev.hmmachinery.dk/en/product/belt-grinder-673>