

Centerless belt grinder - dry version

00103362

TAS Centerless grinders - TAS 75CG

HM TAS 75CG a combined belt and centerless grinder for all kind of pipe and tubes HM TAS 75CG is supplied with an attachment which can be mounted on all belt grinders with a 75x2000 mm belt and with a large grinding surface on top.

The centerless grinding attachment is easy to operate and grinds/polishes all pipes and tubes with diameters of between 6 and 120 mm.

HM TAS 75CG centerless grinding and polishing machine is unique compared to other centerless grinders on the market because it remain a belt grinder even when the centreless grinding attachment is mounted.

It is not necessary to take off the centerless attachment when using the belt grinder for normal grinding work.

Both the contact wheel and the flat grinding surface on top are available for normal grinding and polishing even with the attachment on the machine.

Support stands are available as extra accessory for long pipes and tubes.

Product Link:

<https://dev.hmmachinery.dk/en/product/centerless-belt-grinder-dry-version-678>

Product Specification

Motor (HP)	4,1
Voltage	3x400V-50 Hz
Wheel size, Drive wheel (∅ mm)	200x75x24
Wheel size, Contact wheel (∅ mm)	200x75x20
Support roller (mm)	35x90x23
Wheel size, Polishing wheel (∅ mm)	50x150x25
Gear	NMRV 030
Pipe dimension (∅ mm)	6-120
Number of spindle speeds	1
Without exhaust	1
Length (mm)	1050
Width (mm)	700
Height (mm)	1150
Net weight (kg)	80

Product Link:

<https://dev.hmmachinery.dk/en/product/centerless-belt-grinder-dry-version-678>